

Power Blade Cable Cutter Head








For Almost Any Drill Heavy Duty Cable Cutter













Product Feature:

Power blade cable cutter head no need to mess with battery packs or special chargers, this tool works with the drill you already carry. The blade is sharper and the stability of feeding is stronger. The operation is convenient, light and smart. New way to cut cable that reduces fatigue, tool cost and space. *Drill not included.






Cutter Head Description(Warning: Match the drill equal or greater than 50 Nm torque)

| Type | Weight | Max. die | Dimension | Suitable Scope |
|--|--------|----------|--------------|--|
|  DDQ30ASS | 4.58kg | 30mm | 290*200*95mm | Cutting steel lock |
|  DDQ30T | 3.15kg | 30mm | 210*140*90mm |  鐵管 iron pipe Cutting iron tube below 30mm |
|  DDQ55AS | 5.1kg | 55mm | 340*210*95mm |  銅芯電纜 cable 鋁裝電纜 armored cable cutting Cu-Al armored cable below 55mm |
|  DDQ30AS | 4.58kg | 30mm | 290*200*95mm |  銅芯電纜 cable 鋁裝電纜 armored cable 鋼芯鋁絞線 ACSR cutting ACSR below 30mm (400mm ²) or prestressed steel wire below 10mm |

| | | | | |
|---|-------|-------|--------------|---|
|  DDQ100A | 5.4kg | 100mm | 320*280*95mm |  銅芯電纜 cable 鎧裝電纜 armored cable cutting Cu-Al armored cable below 100mm |
|  DDQ100 | 4.0kg | 100mm | 280*260*90mm |  銅芯電纜 cable 鎧裝電纜 armored cable cutting Cu-Al armored cable below 100mm |
|  DDQ80A | 5.3kg | 80mm | 310*260*95mm |  銅芯電纜 cable 鎧裝電纜 armored cable Cutting armored cable below 80mm |
|  DDQ80 | 3.9kg | 80mm | 260*260*90mm |  銅芯電纜 cable 鎧裝電纜 armored cable Cutting armored cable below 80mm |
|  DDQ56A | 4.2kg | 56mm | 260*210*95mm |  銅芯電纜 cable 鎧裝電纜 armored cable 海底電纜 seabed cable cutting reinforced armored cable or seabed cable below 56mm |
|  DDQ56 | 3.0kg | 56mm | 220*220*90mm |  銅芯電纜 cable 鎧裝電纜 armored cable 海底電纜 seabed cable cutting reinforced armored cable or seabed cable below 56mm |

| | | | | |
|---|------------|--------|--------------|--|
|  DDQ55A | DDQ55 A | DDQ55A | DDQ55A |  銅芯電纜 cable 鎧裝電纜 armored cable Cutting Cu-Al armored cable below 55mm |
|  DDQ55 | 3.1kg | 55mm | 220*220*90mm |  銅芯電纜 cable 鎧裝電纜 armored cable cutting Cu-Al armored cable below 55mm |
|  DDQ45A | 4.3kg | 45mm | 260*210*95mm |  銅芯鋁絞線 ACSR Cutting ACSR below 45mm(1440mm ²) |
|  DDQ45 | 2.8kg | 45mm | 220*220*90mm |  銅芯鋁絞線 ACSR Cutting ACSR below 45mm(1440mm ²) |
|  DDQ35A | 4.2kg | 35mm | 270*200*95mm |  銅芯電纜 cable 鎧裝電纜 armored cable cutting Cu-Al armored cable below 35mm |

| | | | | |
|---|--------|------|--------------|--|
|  <p>DDQ35</p> | 2.75kg | 35mm | 200*200*90mm |  <p>銅芯電纜 cable 鎧裝電纜 armored cable</p> <p>cutting Cu-Al armored cable below 35mm</p> |
|  <p>DDQ33A</p> | 4.2kg | 22mm | 270*200*95mm |  <p>銅芯電纜 cable 鋼絲繩 steel wire ropes</p> <p>Cutting steel ropes below 22mm</p> |
|  <p>DDQ33</p> | 2.77kg | 22mm | 200*200*90mm |  <p>銅芯電纜 cable 鋼絲繩 steel wire ropes</p> <p>Cutting steel wire ropes below 22mm</p> |
|  <p>DDQ30A</p> | 4.2kg | 30mm | 270*200*95mm |  <p>電纜 reinforced steel bar 鋼絲繩 chain 鋼芯的絞線 ACSR 銅芯電纜 cable 鋼絞線 prestressed wire</p> <p>cutting ACSR below 30mm, Cu-Al cable ,Prestressed steel wire, reinforced steel bar or chain below 10mm</p> |
|  <p>DDQ30</p> | 2.76kg | 30mm | 200*200*90 |  <p>銅芯電纜 cable 鋼芯的絞線 ACSR 鋼絞線 prestressed wire 鋼絲繩 chain 電纜 reinforced steel bar</p> <p>cutting ACSR below 30mm, Cu-Al cable ,Prestressed steel wire, reinforced steel bar or chain below 10mm</p> |

THE OPERATING PHOTO:

