

## Split-unit Hydraulic Crimpers

### Directions of Product

#### Uses and performance:

Split-unit hydraulic crimpers consists of two parts of manual oil pump and crimp connection work head. Oil delivery hose adopts rapid joint, which is reliable in sealing and easy to fix and dismantle. Manual oil pump adopts compound pump, which has a big flow and fast current velocity in case of free load and a small flow and current velocity in case of heavy load. The product is a necessary tool of connecting conductor ends to be used in line construction, equipment installation for power supply department and factories and mines and maintenance. It is both suitable for indoor and outdoor operations.



#### Appoints for attention:

1. In case that oil pump is under idle running, please replenish it in time.
2. During crimp connecting, please see to if the pres die is in conformity with the pliers.
3. Overload using is prohibited and properly uses pliers.
4. The head of pliers can be mated with power oil pump.
- 5.

#### Technical Parameters:

Model	Contact Mould(mm <sup>2</sup> )		Max. Pressure (T)	Max. Stroke (mm)	Size of contact mould(mm <sup>2</sup> )	Piston Return
	Al terminal	Cu terminal				
WXY-1000F	400-800	400-1000	45	30	400,500,630,800,1000	Auto-reset
WXY-630F	240-500	240-630	25	22	240,300,400,500,630	
WXY-500	70-400	70-500	20	22	70,95,120,150,185,240,300,400,500	Hydraulic Fluid
WXY-400AF	70-300	70-400	16	25	70,95,120,150,185,240,300,400	
WXY-300CF	16-240	16-300	14	30	16,25,35,50,70,95,120,150,185,240,300	32# lubricant
WXY-300BF	16-240	16-300	14	20		
WXY-510F	50-300	50-400	16	32	50,70,95,120,150,185,240,300,400	
WXY-240BF	16-185	16-240	14	20	16,25,35,50,70,95,120,150,185,240	
WXY-35F	50-185	50-300	16	32	50,70,95,120,150,185,240,300	
WXY-430F	50-185	50-400	16	32	50,70,95,120,150,185,240,300,400	